



### Dimensions

|                  |           |
|------------------|-----------|
| Weight:          | 86.00 lbs |
| Internal Length: | 24.00 in  |
| Internal Width:  | 19.00 in  |
| Internal Height: | 14.00 in  |
| External Length: | 36.00 in  |
| External Width:  | 26.75 in  |
| External Height: | 23.25 in  |
| Lid Height:      | 4.50 in   |
| Bottom Depth:    | in        |

### Features

SKB Lifetime Warranty  
Pressure relief valve  
Recessed black powder coated stainless steel hardware  
Completely removable frame  
Front doors are 2" deep, Rear doors are 5" deep  
Standard Rack depth 24" rail to rail  
Standard 19" Rack width per ANSI/EIA-310-C  
Molded in stacking ribs and lugs  
8 comfort grip spring loaded lift handles  
Rotationally molded case  
Case coupling straps and lid hangers  
Meets or exceeds MIL-STD 810G  
Square hold rack rails to accommodate either #10-32 US standard, or 6mm int. standard cage nuts

## All Options and Accessories

Small Access. Pocket - Uninstalled (20"x10"x 3") (\$84.99)

Large Access. Pocket - Uninstalled (20"x15"x3") (\$94.99)

Caster Accessory Bag (\$94.99)

Shipping Label Plate (\$34.99)

40 - 150 lbs. (\$0.00)

150+ lbs. - Contact Allcases for Assistance Before Ordering (\$0.00)

## Certificates and Downloads

[RESK-3SKB-R908U24](#)

[SKB 24" Shock Racks](#)