



Dimensions

Weight:	90 lbs
Internal Length:	24 in
Internal Width:	19 in
Internal Height:	19.25 in
External Length:	in
External Width:	in
External Height:	in
Lid Height:	2 (Front) in
Bottom Depth:	in

Features

Standard Case Features: SKB Lifetime Warranty Pressure relief valve Recessed black powder coated stainless steel hardware Completely removable frame Front doors are 2" deep, Rear doors are 5" deep Standard Rack depth 24" rail to rail Standard 19" Rack width per ANSI/EIA-310-C Molded in stacking ribs and lugs 8 comfort grip spring loaded lift handles Rotationally molded case Case coupling straps and lid hangers Meets or exceeds MIL-STD 810G Square hold rack rails to accommodate either #10-32 US standard, or 6mm int. standard cage nuts

All Options and Accessories

Small Access. Pocket - Uninstalled (20"x10"x 3") (\$84.99)

Large Access. Pocket - Uninstalled (20"x15"x3") (\$94.99)

Caster Accessory Bag (\$94.99)

Shipping Label Plate (\$34.99)

40 - 150 lbs. (\$0.00)

150+ lbs. - Contact Allcases for Assistance Before Ordering (\$0.00)

Certificates and Downloads

[RESK-3RR-11U24-25B](#)

[SKB 3RR Sliding Rack Case](#)